

EMI RFI FILTERS



B01 PACKAGE

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C14
Output terminals	: Faston 6.3 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



PANEL MOUNTING SINGLE STAGE

B02 PACKAGE

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C14
Output terminals	: Faston 6.3 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



B03 PACKAGE

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C14
Output terminals	: Faston 6.3 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



B04 PACKAGE

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C14 with red illuminated switch & fuse
Output terminals	: Faston 4.8 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus





B05 PACKAGE

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C14 with red non-illuminated switch and single fuse
Output terminals	: Faston 6.3 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



B06 PACKAGE

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C14 with black non-illuminated switch & double fuse
Output terminals	: Faston 6.3 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

B07 PACKAGE

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C14 with single fuse
Output terminals	: Faston 6.3 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



B08 PACKAGE

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C14 with double fuse
Output terminals	: Faston 6.3 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

B14 PACKAGE

Rated Current	: 1A, 3A, 6A, 10A, 15A, 20A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C20
Output terminals	: Faston 6.3 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS





B15 PACKAGE

Rated Current	: 1A, 3A, 6A,10A,15A,20A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C20
Output terminals	: Faston 6.3 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



PANEL MOUNTING DOUBLE STAGE

B14 PACKAGE

Rated Current	: 1A, 3A, 6A,10A,15A,20A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C20
Output terminals	: Faston 6.3 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS



B15 PACKAGE

Rated Current	: 1A, 3A, 6A,10A,15A,20A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Inlet	: C20
Output terminals	: Faston 6.3 x 0.8 / solder tab
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



CABLE MOUNT

D01 PACKAGE

Rated Current	: 5A, 6A, 10A, 15A
Rated Voltage	: 120/250VAC
Mounting	: Cable Mounting
Operating Temperature	: 40°C/-25° +85°C
Input terminals	: Open end, Indian plug, IEC connector
Output terminals	: Open end, IEC connector
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



**CHASSIS FILTER****B09 PACKAGE**



Rated Current	: 16A
Rated Voltage	: 120/250VAC
Mounting	: Chassis Mounting
Input terminals	: Faston 6.3 x 0.8 / solder tab
Output terminals	: Faston 6.3 x 0.8 / solder tab
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

**DIN-RAIL MOUNTING****E03 PACKAGE**

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Din-Rail mounting
Input terminals	: Wire leads
Output terminals	: Wire leads
Operating Temperature	: 40°C/-25° +85°C
Compliance Marking	: CE, RoHS

E06 PACKAGE

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Din-Rail mounting
Input terminals	: Faston 6.3 x 0.8 / solder tab
Output terminals	: Faston 6.3 x 0.8 / solder tab
Operating Temperature	: 40°C/-25° +85°C
Compliance Marking	: CE, RoHS

**DIN RAIL MOUNTING-3 PHASE 4 WIRE FILTER****E07 PACKAGE**


Rated Current	: 3A, 6A, 10A, 15A, 20A, 30A, 40A
Rated Voltage	: 250VAC (Phase-Neutral) 440VAC (Phase-Phase)
Mounting	: Din-Rail mounting
Input terminals	: Screw terminal/ Busbar terminal/ Touch Safe terminal/Wire terminal
Output terminals	: Screw terminal/ Busbar terminal/ Touch Safe terminal/Wire terminal
Operating Temperature	: 40°C/-25° +85°C
Compliance Marking	: CE, RoHS

**C01 PACKAGE****CHASSIS MOUNTING SINGLE PHASE SINGLE STAGE FILTER**

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Chassis Mounting
Input terminals	: Faston 6.3 x 0.8 / solder tab
Output terminals	: Faston 6.3 x 0.8 / solder tab
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

**C02 PACKAGE**

Rated Current	: 1A, 3A, 6A, 10A, 15A, 20A
Rated Voltage	: 120/250VAC
Mounting	: Chassis Mounting
Input terminals	: Faston 6.3 x 0.8 / solder tab
Output terminals	: Faston 6.3 x 0.8 / solder tab
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

**C03 PACKAGE**

Rated Current	: 1A, 3A, 6A, 10A
Rated Voltage	: 120/250VAC
Mounting	: Chassis Mounting
Input terminals	: Faston 4.8 x 0.8 / solder tab
Output terminals	: Faston 4.8 x 0.8 / solder tab
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

**C09 PACKAGE**

Rated Current	: 20A, 30A, 40A, 50A
Rated Voltage	: 120/250VAC
Mounting	: Chassis Mounting
Input terminals	: Busbar terminal
Output terminals	: Busbar terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

**C09 PACKAGE**

Rated Current	: 20A, 30A, 40A, 50A 60A
Rated Voltage	: 120/250VAC
Mounting	: Chassis Mounting
Input terminals	: Screw terminal
Output terminals	: Screw terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus





C02 PACKAGE

CHASSIS MOUNTING SINGLE PHASE DOUBLE STAGE FILTER

Rated Current : 3A, 6A, 10A, 15A, 20A
Rated Voltage : 120/250VAC
Mounting : Chassis Mounting
Input terminals : Faston 6.3 x 0.8 / solder tab
Output terminals : Faston 6.3 x 0.8 / solder tab
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)


Compliance Marking : CE, RoHS
Approvals : cCSAus



C09 PACKAGE

Rated Current : 20A, 30A, 40A, 50A 60A
Rated Voltage : 120/250VAC
Mounting : Chassis Mounting
Input terminals : Screw terminal
Output terminals : Screw terminal
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)


Compliance Marking : CE, RoHS
Approvals : cCSAus



C10 PACKAGE

Rated Current : 50A, 60A
Rated Voltage : 120/250VAC
Mounting : Chassis Mounting
Input terminals : Screw terminal
Output terminals : Screw terminal
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)

Compliance Marking : CE, RoHS
Approvals : cCSAus



C11 PACKAGE

Rated Current : 80A, 100A, 120A, 150A
Rated Voltage : 120/250VAC
Mounting : Chassis Mounting
Input terminals : Screw terminal
Output terminals : Screw terminal
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)

Compliance Marking : CE, RoHS
Approvals : cCSAus



C12 PACKAGE

Rated Current : 180A, 200A, 250A
Rated Voltage : 120/250VAC
Mounting : Chassis Mounting
Input terminals : Screw terminal
Output terminals : Screw terminal
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)

Compliance Marking : CE, RoHS
Approvals : cCSAus






CHASSIS MOUNTING 3 PHASE 3 WIRE FILTER (WITHOUT NEUTRAL)

C35 PACKAGE

Rated Current	: 3A, 6A, 10A, 15A, 20A, 30A, 40A
Rated Voltage	: 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Screw terminal
Output terminals	: Screw terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005 CSA Std. C22.2 No. 8-13, UL 1283 (5th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus





C35 PACKAGE

Rated Current	: 3A, 6A, 10A, 15A, 20A, 30A, 40A
Rated Voltage	: 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Touch Safe terminal
Output terminals	: Touch Safe terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA Std. C22.2 No. 8-13, UL 1283 (5th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

CHASSIS MOUNTING 3 PHASE 3 WIRE FILTER

C37 PACKAGE

Rated Current	: 50A, 60A, 80A
Rated Voltage	: 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Screw terminal
Output terminals	: Screw terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (5th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



C37 PACKAGE

Rated Current	: 50A, 60A, 80A
Rated Voltage	: 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Wire terminal
Output terminals	: Wire terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (5th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus




C39 PACKAGE

Rated Current	: 100A, 120A, 150A
Rated Voltage	: 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Screw terminal/ Busbar terminal/ Touch Safe terminal/ Wire terminal
Output terminals	: Screw terminal/ Busbar terminal/ Touch Safe terminal/ Wire terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (5th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus




C41 PACKAGE

Rated Current	: 180A, 200A, 250A
Rated Voltage	: 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Screw terminal/ Busbar terminal/Touch Safe terminal/Wire terminal
Output terminals	: Screw terminal/ Busbar terminal/Touch Safe terminal/Wire terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (5th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus




C43 PACKAGE

Rated Current	: 300A, 350A, 400A, 450A
Rated Voltage	: 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Busbar terminal
Output terminals	: Busbar terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (5th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



C44 PACKAGE

Rated Current	: 500A, 550A, 600A, 650A
Rated Voltage	: 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Busbar terminal
Output terminals	: Busbar terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (5th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus






C57 PACKAGE

Rated Current : 700A, 800A, 1000A
Rated Voltage : 440VAC (Phase-Phase)
Mounting : Chassis Mounting
Input terminals : Busbar terminal
Output terminals : Busbar terminal
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)


Compliance Marking : CE, RoHS
Approvals : cCSAus



C47 PACKAGE

Rated Current : 1200A, 1400A, 1600A
Neutral : Without neutral
Rated Voltage : 440VAC (Phase-Phase)
Mounting : Chassis Mounting
Input terminals : Busbar terminal
Output terminals : Busbar terminal
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)

Compliance Marking : CE, RoHS
Approvals : cCSAus



C71 PACKAGE CHASSIS MOUNTING 3 PHASE 4 WIRE FILTER (WITH NEUTRAL)

Rated Current : 3A, 6A, 10A, 15A, 20A, 30A, 40A
Rated Voltage : 250 VAC (Phase-Neutral) 440VAC (Phase-Phase)
Mounting : Chassis Mounting
Input terminals : Screw terminal
Output terminals : Screw terminal
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)

Compliance Marking : CE, RoHS
Approvals : cCSAus



C71 PACKAGE

Rated Current : 3A, 6A, 10A, 15A, 20A, 30A, 40A
Rated Voltage : 250 VAC (Phase-Neutral) 440VAC (Phase-Phase)
Mounting : Chassis Mounting
Input terminals : Busbar terminal
Output terminals : Busbar terminal
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)


Compliance Marking : CE, RoHS
Approvals : cCSAus



C74 PACKAGE

Rated Current : 50A, 60A, 80A
Rated Voltage : 250 VAC (Phase-Neutral) 440VAC (Phase-Phase)
Mounting : Chassis Mounting
Input terminals : Screw terminal
Output terminals : Screw terminal
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)

Compliance Marking : CE, RoHS
Approvals : cCSAus




**C74 PACKAGE**

Rated Current	: 50A, 60A, 80A
Rated Voltage	: 250 VAC (Phase-Neutral) 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Busbar terminal
Output terminals	: Busbar terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

**C76 PACKAGE**

Rated Current	: 100A, 120A, 150A
Rated Voltage	: 250 VAC (Phase-Neutral) 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Screw terminal/ Busbar terminal/Touch Safe terminal/Wire terminal
Output terminals	: Screw terminal/ Busbar terminal/Touch Safe terminal/Wire terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus


Rated Current	: 180A, 200A, 250A
Rated Voltage	: 250 VAC (Phase-Neutral) 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Screw terminal/ Busbar terminal/Touch Safe terminal/Wire terminal
Output terminals	: Screw terminal/ Busbar terminal/Touch Safe terminal/Wire terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

C78 PACKAGE**C83 PACKAGE**

Rated Current	: 300A, 350A, 400A, 450A, 500A, 550A, 600A, 650A
Rated Voltage	: 250 VAC (Phase-Neutral) 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Busbar terminal
Output terminals	: Busbar terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

C84 PACKAGE

Rated Current	: 700A, 800A, 1000A
Rated Voltage	: 250 VAC (Phase-Neutral) 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Busbar terminal
Output terminals	: Busbar terminal
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (7th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus






A01 PACKAGE


Rated Current : 1A, 3A, 6A, 10A
Rated Voltage : 120/250VAC
Mounting : PCB Mounting
Input terminals : Solder lug
Output terminals : Solder lug
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2
NO. 8-13, UL 1283 (7th Edition)
Compliance Marking : CE, RoHS
Approvals : cCSAus

PCB MOUNTING SINGLE PHASE FILTER



A02 PACKAGE

Rated Current : 1A, 3A, 6A
Rated Voltage : 120/250VAC
Mounting : PCB Mounting
Input terminals : Solder lug
Output terminals : Solder lug
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2
NO. 8-13, UL 1283 (7th Edition)
Compliance Marking : CE, RoHS
Approvals : cCSAus



A03 PACKAGE

Rated Current : 1A, 3A, 6A, 10A
Rated Voltage : 120/250VAC
Mounting : PCB Mounting
Input terminals : Solder lug
Output terminals : Solder lug
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2
NO. 8-13, UL 1283 (7th Edition)
Compliance Marking : CE, RoHS
Approvals : cCSAus



PCB MOUNTING SINGLE PHASE FILTER

A04 PACKAGE


Rated Current : 2A, 6A
Rated Voltage : 120/250VAC
Mounting : PCB Mounting
Input terminals : Solder lug
Output terminals : Solder lug
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2
NO. 8-13, UL 1283 (7th Edition)
Compliance Marking : CE, RoHS
Approvals : cCSAus



A04 PACKAGE

PCB MOUNTING 3 PHASE 3 WIRE FILTER (WITHOUT NEUTRAL)

Rated Current : 1A, 2A, 3A, 6A, 10A
Rated Voltage : 440VAC (Phase-Phase)
Mounting : PCB Mounting
Input terminals : Solder lug
Output terminals : Solder lug
Operating Temperature : 40°C/-25° +85°C
Reference Standard : EN60939-3:2015 & EN60939-2:2005, CSA C22.2
NO. 8-13, UL 1283 (5th Edition)
Compliance Marking : CE, RoHS
Approvals : cCSAus





EMI RFI FILTERS OUTPUT FILTER CUSTOMIZE FILTER

PCB MOUNTING 3 PHASE 3 WIRE FILTER (WITHOUT NEUTRAL)


A04 PACKAGE

Rated Current	: 1A, 2A, 3A, 6A, 10A
Rated Voltage	: 250 VAC (Phase-Neutral) 440VAC (Phase-Phase)
Mounting	: PCB Mounting
Input terminals	: Solder lug
Output terminals	: Solder lug
Operating Temperature	: 40°C/-25° +85°C
Reference Standard	: EN60939-3:2015 & EN60939-2:2005, CSA C22.2 NO. 8-13, UL 1283 (5th Edition)
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



OUTPUT FILTER

CHASSIS MOUNTING 3 PHASE 3 WIRE FILTER



C91 PACKAGE

Rated Current	: 12A
Rated Voltage	: 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Touch safe terminal
Output terminals	: Touch safe terminal
Operating Temperature	: 40°C/-25° +85°C
Compliance Marking	: CE, RoHS




CUSTOMISED FILTER

SINGLE PHASE PANEL MOUNTING FILTER

B10 Package

Rated Current	: 3A
Rated Voltage	: 120/250VAC
Mounting	: Panel mounting
Operating Temperature	: 40°C/-25° +85°C
Input terminals	: Circular MIL connector
Output terminals	: Faston 6.3 x 0.8 / solder tab





C02 PACKAGE

Rated Current : 1A, 3A, 6A, 10A, 15A, 20A
Rated Voltage : 120/250VAC
Mounting : Chassis Mounting
Operating Temperature : 40°C/-25° +85°C
Input terminals : Wire lead terminal
Output terminals : Wire lead terminal
Compliance Marking : CE, RoHS

CHASSIS MOUNTING SINGLE PHASE FILTER





A03 PACKAGE

Rated Current : 1A, 3A, 6A, 10A
Rated Voltage : 120/250VAC
Mounting : Chassis Mounting
Input terminals : Solder lug
Output terminals : Solder lug
Operating Temperature : 40°C/-25° +85°C
Compliance Marking : CE, RoHS

C06 PACKAGE

Rated Current : 1A, 3A, 6A, 10A, 15A, 20A
Rated Voltage : 120/250VAC
Mounting : Chassis Mounting
Input terminals : Wire terminal
Output terminals : Wire terminal
Operating Temperature : 40°C/-25° +85°C
Compliance Marking : CE, RoHS




C08 PACKAGE

Rated Current : 10A, 20A, 30A, 40A
Rated Voltage : 120/250VAC
Mounting : Chassis Mounting
Input terminals : Busbar terminal
Output terminals : Busbar terminal
Operating Temperature : 40°C/-25° +85°C
Compliance Marking : CE, RoHS

C14 PACKAGE


Rated Current : 3A
Rated Voltage : 120/250VAC
Mounting : Chassis Mounting
Input terminals : Wire lead terminal
Output terminals : Wire lead terminal
Operating Temperature : 40°C/-25° +85°C
Compliance Marking : CE, RoHS






C19 PACKAGE

Rated Current	: 20A
Rated Voltage	: 120/250VAC
Mounting	: Chassis Mounting
Input terminals	: Screw terminal/ Busbar terminal
Output terminals	: Screw terminal/ Busbar terminal
Operating Temperature	: 40°C/-25° +85°C
Compliance Marking	: CE, RoHS



CHASSIS MOUNTING 3 PHASE 3 WIRE FILTER (WITHOUT NEUTRAL)





C48 PACKAGE

Rated Current	: 25A, 40A
Rated Voltage	: 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Touch Safe terminal
Output terminals	: Touch Safe terminal
Operating Temperature	: 40°C/-25° +85°C
Compliance Marking	: CE, RoHS

C49 PACKAGE

Rated Current	: 5A, 7A
Rated Voltage	: 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Touch Safe terminal
Output terminals	: Wire lead terminal
Operating Temperature	: 40°C/-25° +85°C
Compliance Marking	: CE, RoHS



C51 PACKAGE

Rated Current	: 140A
Rated Voltage	: 480VAC
Mounting	: Chassis Mounting
Input terminals	: Touch Safe terminal
Output terminals	: Wire lead terminal
Operating Temperature	: 40°C/-25° +85°C
Compliance Marking	: CE, RoHS

CHASSIS MOUNTING 3 PHASE 4 WIRE FILTER (WITH NEUTRAL)

C72 PACKAGE

Rated Current	: 20A, 30A, 40A
Rated Voltage	: 250 VAC (Phase-Neutral) 440VAC (Phase-Phase)
Mounting	: Chassis Mounting
Input terminals	: Touch safe terminal
Output terminals	: Touch safe terminal
Operating Temperature	: 40°C/-25° +85°C
Compliance Marking	: CE, RoHS

