

NEMA CONNECTORS



NEMA TWIST LOCK PLUGS

ENP-LD5-20

Connector Type	: Twist lock L5-20P type
Rated Current	: 20A
Rated Voltage	: 125V AC
Mounting	: NA
Operating Temperature	: 0°C TO 75°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 No.42-10
Compliance Marking	: RoHS
Approvals	: cULus



ENP-LD6-20

Connector Type	: Twist lock L6-20P type
Rated Current	: 20A
Rated Voltage	: 250V AC
Mounting	: NA
Operating Temperature	: 0°C TO 75°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 No.42-10
Compliance Marking	: RoHS
Approvals	: cULus



ENP-LD5-30

Connector Type	: Twist lock L5-30P type
Rated Current	: 30A
Rated Voltage	: 125V AC
Mounting	: NA
Operating Temperature	: 0°C TO 75°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 No.42-10
Compliance Marking	: RoHS
Approvals	: cULus



ENP-LD6-30

Connector Type	: Twist lock L6-30P type
Rated Current	: 30A
Rated Voltage	: 250V AC
Mounting	: NA
Operating Temperature	: 0°C TO 75°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 No.42-10
Compliance Marking	: RoHS
Approvals	: cULus





ENP-LD21-20

Connector Type	: Twist lock L21-20P type
Rated Current	: 20A
Rated Voltage	: 208V AC
Mounting	: NA
Operating Temperature	: 0°C TO 75°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 No.42-10
Compliance Marking	: RoHS
Approvals	: cULus



ENP-LD21-30

Connector Type	: Twist lock L21-30P type
Rated Current	: 30A
Rated Voltage	: 208V AC
Mounting	: NA
Operating Temperature	: 0°C TO 75°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 No. 42-10
Compliance Marking	: RoHS
Approvals	: cULus

NEMA 3 GANG RECEPTACLE

ENO-0515-33-X

Connector Type	: 5-15R Type
Rated Current	: 15A
Rated Voltage	: 125V AC
Mounting	: Panel, Snap mounting
Operating Temperature	: 0°C TO 75°C* on request upto 125°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 NO. 182.3
Compliance Marking	: RoHS
Approvals	: cULus



ENO-0515-43-X

Connector Type	: 5-15R Type
Rated Current	: 15A
Rated Voltage	: 125V AC
Mounting	: Panel, Snap mounting
Operating Temperature	: 0°C TO 75°C* on request upto 125°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 NO. 182.3
Compliance Marking	: RoHS
Approvals	: cULus



NEMA CONNECTORS

ENO-0520-33-X

Connector Type	: 5-20R Type
Rated Current	: 20A
Rated Voltage	: 125V AC
Mounting	: Panel, Snap mounting
Operating Temperature	: 0°C TO 75°C* on request upto 125°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 NO. 182.3
Compliance Marking	: RoHS
Approvals	: cULus



NEMA 4 GANG RECEPTACLE

ENO-0520-43-X

Connector Type	: 5-20R Type
Rated Current	: 20A
Rated Voltage	: 125V AC
Mounting	: Panel, Snap mounting
Operating Temperature	: 0°C TO 75°C* on request upto 125°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 NO. 182.3
Compliance Marking	: RoHS
Approvals	: cULus



NEMA RECEPTACLE

ENO-1112

Connector Type	: 5-20R Type
Rated Current	: 20A
Rated Voltage	: 125V AC
Mounting	: Panel, Snap mounting
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 NO. 182.3
Compliance Marking	: RoHS
Approvals	: cULus



NEMA TWIST LOCK RECEPTACLE

ENO-3112 SERIES

Connector Type	: L5-20R Type
Rated Current	: 20A
Rated Voltage	: 125V
Mounting	: Panel, Screw-type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: UL-498, UL-486E, NEMA WD 6, CAN/CSA C22.2 No.0-M91, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cULus, cCSAus





ENO-3113 SERIES

Connector Type	: L5-30R Type
Rated Current	: 30A
Rated Voltage	: 125V
Mounting	: Panel, Screw-type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: UL-498, UL-486E, NEMA WD 6, CAN/CSA C22.2 No.0-M91, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cULus, cCSAus



ENO-3112-R, ENO-3112-F-R

Connector Type	: L5-30R Type
Rated Current	: 30A
Rated Voltage	: 125V
Mounting	: Panel, Screw-type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: UL-498, UL-486E, NEMA WD 6, CAN/CSA C22.2 No.0-M91, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cCSAus

ENO-3122 SERIES

Connector Type	: L6-20R Type
Rated Current	: 20A
Rated Voltage	: 250V
Mounting	: Panel, Screw-type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: UL-498, UL-486E, NEMA WD 6, CAN/CSA C22.2 No.0-M91, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cULus, cCSAus



NEMA TWIST LOCK RECEPTACLE-PCB TERMINAL



ENO-3122-P-X

Connector Type	: Twist lock L6-20R PCB type
Rated Current	: 20A
Rated Voltage	: 250 V
Mounting	: Panel, Screw & PCB type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cULus approval





NEMA TWIST LOCK RECEPTACLE

ENO-3122-X

Connector Type	: Twist lock L6-20R type
Rated Current	: 20A
Rated Voltage	: 250 V
Mounting	: Panel, Screw type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: UL-498, UL-486E, NEMA WD 6, CAN/CSA C22.2 No.0-M91, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cULus, cCSAus



ENO-3123 SERIES

Connector Type	: Twist lock L6-30R type
Rated Current	: 30A
Rated Voltage	: 250 V
Mounting	: Panel, Screw type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: UL-498, UL-486E, NEMA WD 6, CAN/CSA C22.2 No.0-M91, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cULus, cCSAus



NEMA TWIST LOCK RECEPTACLE-PCB TERMINAL

ENO-3123-P-X

Connector Type	: Twist lock L6-30R PCB Mounted type
Rated Current	: 30A
Rated Voltage	: 250 V
Mounting	: Panel, Screw type & PCB type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: UL-498, NEMA WD 6, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cULus, cCSAus



NEMA TWIST LOCK RECEPTACLE

ENO-3123X

Connector Type	: Twist lock L6-30R type
Rated Current	: 30A
Rated Voltage	: 250 V
Mounting	: Panel, Screw type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: UL-498, UL-486E, NEMA WD 6, CAN/CSA C22.2 No.0-M91, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cULus, cCSAus



ENO-4123

Connector Type	: Twist lock L14-30R type
Rated Current	: 30A
Rated Voltage	: 125/250 V
Mounting	: Panel, Screw type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: UL-498, UL-486E, NEMA WD 6, CAN/CSA C22.2 No.0-M91, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cULus, cCSAus





NEMA SOCKET

ENO-3123-F

Connector Type	: Twist lock L6-30R type
Rated Current	: 30A
Rated Voltage	: 250 V
Mounting	: Panel, Screw type
Operating Temperature	: 0°C TO 65°C * on request upto 125°C
Reference Standard	: 486E, NEMA WD 6, CAN/CSA C22.2 No.0-M91, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cULus, cCSAus



ENO-3113-F


Connector Type	: Twist lock L5-30R type
Rated Current	: 30A
Rated Voltage	: 125 V
Mounting	: Panel, Screw type
Operating Temperature	: 0°C TO 65°C * on request upto 125°C
Reference Standard	: UL-498, UL-486E, NEMA WD 6, CAN/CSA C22.2 No.0-M91, CSA C22.2 No.42-99
Compliance Marking	: RoHS
Approvals	: cULus, cCSAus



NEMA SOCKET IDC TYPE


ENO-0515-11-X, ENO-0515-12-X

Connector Type	: Nema 5-15R
Rated Current	: 15A
Rated Voltage	: 125 V
Mounting	: Panel, Snap-in type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: NEMA WD 6; UL-498, CSA: 22.2 No. 42-10
Compliance Marking	: RoHS
Approvals	: cULus



ENO-0520-11-X, ENO-0520-12-X

Connector Type	: Nema 5-20R
Rated Current	: 20A
Rated Voltage	: 125 V
Mounting	: Panel, Snap-in type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: NEMA WD 6; UL-498, CSA: 22.2 No. 42-10
Compliance Marking	: RoHS
Approvals	: cULus



ENO-1111-X

Connector Type	: Nema 5-15R
Rated Current	: 15A
Rated Voltage	: 125 V
Mounting	: Panel, Snap-in type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: NEMA WD 6; UL-498, CSA: 22.2 No. 42-10
Compliance Marking	: RoHS
Approvals	: cULus

