



POWER ENTRY COMPONENTS



EMO-11-X

Rated Current	: 10A (VDE)15A (UL)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only} 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus



IEC C13 TYPE OUTLETS



EMO-12-X

Rated Current	: 10A (VDE) 20A (UL) (15A individual & 20A combine)
Rated Voltage	: 250V AC
Type	: 2 Way, C13x2
Mounting	: Panel, Snap-In
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only} 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus

EMO-13-X

Rated Current	: 10A (VDE) 20A (UL) (15A individual & 20A combine)
Rated Voltage	: 250V AC
Type	: 3 Way, C13x3
Mounting	: Panel, Snap-in type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only} 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus



EMO-14-X

Rated Current	: 10A (VDE) 20A (UL) (15A individual & 20A combine)
Rated Voltage	: 250V AC
Type	: 4 Way, C14x4
Mounting	: Panel, Snap-in type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only} 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus



EMO-15-X

Rated Current	: 10A (VDE) 20A (UL) (15A individual & 20A combine)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Type	: 5 Way, C13x5
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only} 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus



EMO-16-X

Rated Current	: 10A (VDE) 20A (UL) (15A individual & 20A combine)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Type	: 6 Way, C13x6
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only} 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus

EMO-17-X

Rated Current	: 10A (VDE) 20A (UL) (15A individual & 20A combine)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Type	: 7 Way, C13x7
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only} 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus



EMO-12G-X

Rated Current	: 10A (VDE) 16A (UL) (12A individual & 16A combine)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Type	: C13x2 Gang
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only} 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus

EMO-14G-X

Rated Current	: 10A (VDE) 16A (UL) (12A individual & 16A combine)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Type	: C13x4 gang
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only} 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus





EMO-16G-X

Rated Current	: 10A (VDE) 20A (UL) (15A individual & 20A combine)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Type	: C13x6 Gang
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only }
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, 0 To 70°C (VDE)
Compliance Marking	: CSA:C22.2 No. 182.3
Approvals	: CE, RoHS
	: VDE, cULus



IEC C19 TYPE OUTLET

EMO-18-X

Rated Current	: 16A (VDE) 20A (UL)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only } 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus



IEC C13 TYPE OUTLET

EMO-21-X

Rated Current	: 10A (VDE) 15A (UL)
Rated Voltage	: 250V AC
Mounting	: Panel, Screw type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only } 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus



IEC C19 TYPE OUTLET

EMO-28-X

Rated Current	: 16A (VDE) 20A (UL)
Rated Voltage	: 250V AC
Mounting	: Panel, Screw type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only } 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus





EMO-182-X

Rated Current	: 16A (VDE) 20A (UL)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Type	: C19x2 Gang
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only }
	: 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus

IEC C19 TYPE OUTLET



IEC SOCKET WITH IDC TERMINALS



EMO-111-X SERIES

Connector Type	: IEC C13 type Outlet
Rated Current	: 15A UL & 10A IEC
Rated Voltage	: 250 V AC
Mounting	: Panel, Snap-in type
Operating Temperature	: 0°C TO 65°C* on request upto 125°C
Reference Standard	: IEC-60320-1, IEC-60320-3, UL-498 & CSA C22.2 No-182.3
Compliance Marking	: RoHS
Approvals	: cULus & TUV

EMI-40-V2

Rated Current	: 10A (VDE) 15A (UL)
Rated Voltage	: 250V AC
Mounting	: NA
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only }
	: 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus

IEC C14 TYPE PLUG CONNECTOR



IEC C20 TYPE PLUG CONNECTOR



EMI-48-V2

Rated Current	: 16A (IEC) 20A (Extended rating)
Rated Voltage	: 250V AC
Mounting	: NA
Operating Temperature	: 0 To 70°C (IEC)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS



EMO-40-V2

Rated Current	: 10A (VDE) 15A (UL)
Rated Voltage	: 250V AC
Mounting	: NA
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only } 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus

IEC C13 TYPE PLUG CONNECTOR



IEC C19 TYPE PLUG CONNECTOR



EMO-48-X

Rated Current	: 16A (IEC) 20A (Extended rating)
Rated Voltage	: 250V AC
Mounting	: NA
Operating Temperature	: 0 To 70°C (IEC)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3
Compliance Marking	: CE, RoHS

EMI-10-X

Rated Current	: 10A (VDE) 15A (UL)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only } 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3-16
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus

IEC C14 TYPE INLETS



EMI-11-X

Rated Current	: 10A
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Function	: with Fuse holder
Operating Temperature	: -25°C To 70°C
Reference Standard	: CSA C22.2 No.60320-1-11, UL 60320-1, IEC 60320-1, IEC 60320-3
Compliance Marking	: CE, RoHS
Approvals	: cCSAus

EMI-12-X,EMI-13-X

Rated Current	: 4A/6A/10A
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Function	: with Switch & Fuse holder
Operating Temperature	: -25° To 70°C
Reference Standard	: CSA C22.2 No.60320-1-11, UL 60320-1, IEC 60320-1, IEC 60320-3
Compliance Marking	: CE, RoHS
Approvals	: cCSAus





EMI-14-X

Rated Current	: 10A (VDE) 15A (UL)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only } 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3-16
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus



EMI-20-X

Rated Current	: 10A (VDE) 15A (UL)
Rated Voltage	: 250V AC
Mounting	: Panel, Screw type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only } 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3-16
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus



EMI-21-X

Rated Current	: 10A
Rated Voltage	: 250V AC
Mounting	: Panel, Screw type
Function	: Inlet With Fuse Holder
Operating Temperature	: -25°C To 70°C
Reference Standard	: CSA C22.2 No.60320-1-11, UL 60320-1, IEC 60320-1, IEC 60320-3
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



EMI-21-DF

Rated Current	: 10A
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Function	: Inlet With Double Fuse Holder
Operating Temperature	: -25°C To 70°C
Reference Standard	: CSA C22.2 No.60320-1-11, UL 60320-1, IEC 60320-1, IEC 60320-3
Compliance Marking	: CE, RoHS
Approvals	: cCSAus



EMI-24-X

Rated Current	: 10A (VDE) 15A (UL)
Rated Voltage	: 250V AC
Mounting	: Panel, Screw type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to 125°C on request for UL only } 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498, CSA:C22.2 No. 182.3-16
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus





EMI-24-H

Rated Current	: 10A , Extended 15A
	: 250V AC
Rated Voltage	: Panel, Screw type
Mounting	: 0 To 65°C (UL) { * Also available up to
Operating Temperature	: 125°C on request for UL only} 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3,
	UL-498, CSA:C22.2 No. 182.3-16
Compliance Marking	: CE, RoHS



EMI-30-X

Rated Current	: 10A (VDE)15A (UL)
Rated Voltage	: 250V AC
Mounting	: PCB & Panel snap-in type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to
	: 125°C on request for UL only}
	: 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3,
	UL-498, CSA:C22.2 No. 182.3-16
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus

IEC C20 TYPE INLETS

EMI-18-X

Rated Current	: 16A (VDE) 20A (UL)
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in type
Type	: C20, C20 With V-Lock
Operating Temperature	: 0 To 65°C (UL) { * Also available up to
	: 125°C on request for UL only} 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498,
	CSA:C22.2 No. 182.3-16
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus



EMI-28-X

Rated Current	: 16A (VDE) 20A (UL)
Rated Voltage	: 250V AC/EMI-28-X
Mounting	: Panel, Screw type
Operating Temperature	: 0 To 65°C (UL) { * Also available up to
	: 125°C on request for UL only}
	: 0 To 70°C (VDE)
Reference Standard	: IEC 60320-1, IEC 60320-3, UL-498,
	CSA:C22.2 No. 182.3-16
Compliance Marking	: CE, RoHS
Approvals	: VDE, cULus





INDIAN SOCKET

EMO-6-X

Rated Current	: 6A
Rated Voltage	: 250VAC
Mounting	: Panel, Snap-in type
Type	: 3 Pin
Operating Temperature	: 0°C TO 70°C
Reference Standard	: IS:1293, IEC-60884-1
Compliance Marking	: ISI, CE, RoHS



EMO-61-X

Rated Current	: 16A / 6A
Rated Voltage	: 250VAC
Type	: 6 Pin
Panel Thickness	: Suitable for 0.2 to 3.0 mm panel thickness
Mounting	: Panel, Snap-in
Operating Temperature	: 0°C TO 70°C
Reference Standard	: IS:1293, IEC-60884-1
Compliance Marking	: ISI, CE, RoHS

EMO-63 SERIES

Rated Current	: 6Amp
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in 0.8-2.0 thk
Type	: 3 Pin
Operating Temperature	: 0 TO 70°C.
Reference Standard	: IS:1293, IEC-60884-1
Compliance Marking	: ISI, CE, RoHS



UNIVERSAL SOCKET



EMO-71 SERIES

Rated Current	: 13Amp
Rated Voltage	: 250V AC
Mounting	: Panel, Snap-in
Function	: 3 Pin OR 2 Pin
Operating Temperature	: 0°C TO 70°C
Reference Standard	: IS:1293, IEC-60884-1
Compliance Marking	: CE, RoHS

EMO-72-4

Rated Current	: 20A
Rated Voltage	: 250V AC
Mounting	: Push-in type,
Operating Temperature	: 0 TO 70°C
Reference Standard	: IS:1293, IEC-60884-1
Compliance Marking	: CE, RoHS

