



TERMINAL & SOCKETS



IDC WIRE TAP CONNECTORS

EWT-A-01

Type	: IDC Wiretap10AWG
Housing Color	: Grey
Rated Current	: 30 Amp
Rated Voltage	: 600 Volts
Recommended Wire Ø	: 5.00 ±0.20
Durability (Mating Cycles Max.)	: 25
Permissible Operating Temperature	: -25°C To 105°C
Compliance	: RoHS,
Compatibility to Mating Part	: Firm Press Fit.
Approval	: UL 486A-486B



EWT-B-06

Type	:IDC Wiretap-12AWG
Housing Color	:Yellow
Rated Current	:20 Amp
Rated Voltage	:600 Volts
Recommended Wire Ø	:4.05 ±0.15
Durability (Mating Cycles Max.)	:25
Permissible Operating Temperature	: -25°C To 105°C
Compliance	:RoHS
Compatibility to Mating Part	:Firm Press Fit.
Approval	:UL 486A-486B



EWT-C-05

Type	:IDC Wiretap-14AWG
Housing Color	:Blue
Rated Current	:15 Amp
Rated Voltage	:600 Volts
Recommended Wire Ø	:3.50 ±0.10
Durability (Mating Cycles Max.)	:25
Permissible Operating Temperature	: -25°C To 105°C
Compliance	:RoHS
Compatibility to Mating Part	:Firm Press Fit.
Approvals	:UL 486A-486B





TERMINAL SOCKETS

BTI-15 SERIES

Rated Current	:15 Amp
Rated Voltage	:250 Volts
Mounting Type	:Panel
Terminals	:Screw Type
Operating temperature	:-20°C to 85°C
Color	:Black/Red/Blue/Yellow/Green
Reference	:JSS 52710
Compliance Marking	:CE, RoHS, cURus (On Request)



ETI-30 SERIES

Rated Current	:30 Amp
Rated Voltage	:250 Volts
Mounting Type	:Panel
Terminals	:Screw Type
Operating temperature	:-20°C to 85°C
Color	:Black/Red/Blue/Yellow/Green
Reference	:JSS 52710
Compliance Marking	:CE, RoHS, cURus (On Request)



TERMINAL BLOCKS

EPTB-1

Type	:Terminal Blocks Series
Rated Current	:63 Amp
Rated Voltage	:450 Volts
Input/Line side	:2AWG to 12AWG
Output/Load side	:12AWG to 18AWG
Number of Inputs	:01
Number of Outputs	:06
Operating temp.	:-40°C to 125°C
Reference standards	:IEC 60947-7-1, UL-486E, UL-1059, UL-1953, CSA:22.2 No.158.
Approvals	:CE, RoHS, cURus



EPTB-2

Type	:Terminal Blocks Series
Rated Current	:63 Amp
Rated Voltage	:450 Volts
Input/Line side	:2AWG to 12AWG
Output/Load side	:12AWG to 18AWG
Number of Inputs	:02
Number of Outputs	:06
Operating temp.	:-40°C to 125°C
Reference standards	:IEC 60947-7-1, UL-486E, UL-1059, UL-1953, CSA:22.2 No.158.
Approvals	:CE, RoHS, cURus





SOCKET

BS-2

Plug Size : Ø2.00MM
Rated Current : 6.3A
Rated Voltage : 250V AC
Mounting : Panel Mount, Screw Type
Operating Temperature : -20°C to +85°C
Reference Standard : JSS 52710
Marking : CE, RoHS (On request)



BS-10

Plug Size : Ø4.00MM
Rated Current : 10A
Rated Voltage : 250V AC
Mounting : Panel Mount, Screw Type
Operating Temperature : -20°C to +85°C
Reference Standard : JSS 52710
Marking : CE, RoHS (On request)

BS-5 SERIES

Plug Size : Ø4.00
Rated Current : 10A
Rated Voltage : 250VAC
Mounting : Panel, Screw-type
Operating Temperature : -20°C to +85°C
Reference Standard : JSS 52710
Marking : CE, RoHS (On request)

