

Reliance Quick Acting Fuses RQB

Mechanical Dimensions

Dimensions	Milimeter
Diameter	5
Length	20

Electrical Characteristic

Rated Current	2.1 In	2.75 In		4 In		10 In
	Max	Min	Max	Min	Max	Max
32 mA to 100 mA (inclusive)	30 min	10 ms	500 ms	3 ms	100 ms	20 ms
Above 100 mA to 10 Amp	30 min	50 ms	2 Sec.	10 ms	300 ms	20 ms

Catalogue Number	Current Rating
RQB 100	100 mA
RQB 125	125 mA
RQB 150	150 mA
RQB 200	200 mA
RQB 250	250 mA
RQB 300	300 mA
RQB 315	315 mA
RQB 350	350 mA
RQB 400	400 mA
RQB 500	500 mA
RQB 630	630 mA
RQB 800	800 mA
RQB 1000	1 A
RQB 1250	1 A 25
RQB 1500	1 A 5
RQB 1600	1 A 6
RQB 2000	2 A
RQB 2500	2 A 5
RQB 3000	3 A
RQB 3150	3 A 15
RQB 4000	4 A
RQB 5000	5 A
RQB 6300	6 A 3
RQB 8000	8 A
RQB 10000	10 A

*
RQB Fuses are low breaking capacity Quick-Acting Fuses manufactured as per CEI/IEC 127-2 and JSS 51901 Style FA02-A