

Reliance Time Lag Fuses RTC

Mechanical Dimensions

Dimensions	Milimeter
Diameter	6.35
Length	32

Electrical Characteristic

Rated Current	2.1 In	2.75 In		4 In		10 In	
	Max	Min	Max	Min	Max	Min	Max
32 mA to 100 mA (inclusive)	2 min	200 ms	10 Sec	40 ms	3 Sec	10 ms	300 ms
Above 100 mA to 10 Amp	2 min	600 ms	10 Sec	150 ms	3 Sec	20 ms	300 ms

Catalogue Number	Current Rating
RTC 032	32 mA
RTC 040	40 mA
RTC 050	50 mA
RTC 063	63 mA
RTC 080	80 mA
RTC 100	100 mA
RTC 125	125 mA
RTC 150	150 mA
RTC 200	200 mA
RTC 250	250 mA
RTC 300	300 mA
RTC 315	315 mA
RTC 350	350 mA
RTC 400	400 mA
RTC 500	500 mA
RTC 630	630 mA
RTC 800	800 mA
RTC 1000	1 A
RTC 1250	1 A 25
RTC 1500	1 A 5
RTC 2000	2 A
RTC 2500	2 A 5
RTC 3000	3 A
RTC 3150	3 A 15
RTC 4000	4 A
RTC 5000	5 A
RTC 6300	6 A 3
RTC 8000	8 A
RTC 10000	10 A

*
RTC Fuses are slow blow/Time Lag Fuses as per Reliance Specification based on CEI/IEC 127-